

Recessed Luminaires



Information management

* Emergency kit + back mirror optional

Astra Fluorescent Luminaires



AR-SN
3001

Recess mounted fluorescent fitting with bright aluminum single parabolic louvers with stepped transversal blades. This insures a high performance with good visual comfort and an economical solution intended for universal use.



AR-SB
3002

Single parabolic bright reflector made of preanodised high quality low iridescence aluminum with christmas tree stepped transversal blades, offering a high light output ratio and a uniform distribution of light flux.



AR-DB
3003

Double parabolic bright reflector made of preanodised, high quality, low iridescence aluminum. This luminaire insures a low luminance at cut-off angles and exceptional visual comfort where extensive use of VDT's is required. The high gloss reflector has a dark light effect.



AR-DM
3004

Double parabolic matt-finish high performance reflector made of preanodised, low iridescence high quality aluminum. This low glare fixture has the advantage of minimizing the contrast between the ceiling and the louver making it suitable for intensive use in VDT areas.



AR-PR
3005

Prismatic methacrylate diffuser enclosed in a tight aluminum frame finished white equipped with a sealing gasket [optional] and spring catches for easy maintenance. IP 44 optional

AR

Functional, high quality recessed luminaires for exposed ceiling grids of 15mm or 24mm T's. Housing made of electrostatically painted sheet steel with white epoxy-polyester powder paint.

The improved efficiency renders this fixture suitable for the intensive use in:

- Banks
- Office areas
- Commercial areas
- Schools
- Hospitals

This fixture is designed and tested according to international norms requirements where all edges are curved for increased security in installation and maintenance.



The wide range of applicable louvers insures a combination of comfort, uniform lighting and improved efficiency [Cat 2].

Each louver is fixed with four springs and can be lowered and hung from either side for maintenance without tools.

Louver code	lamps	L	L1	L2	W	W1	W2	H	D
AR 218	2x18W	595	560	613	295	260	205	90	50
AR 318	3x18W	595	560	613	595	560	505	90	50
AR 418	4x18W	595	560	613	595	560	505	90	50
AR 136	1x36W	1195	1170	1123	295	260	205	90	50
AR 236	2x36W	1195	1170	1123	295	260	205	90	50
AR 336	3x36W	1195	1170	1123	595	560	505	90	50
AR 436	4X36W	1195	1170	1123	595	560	505	90	50

LOUVER MODEL

code	louver	alum. material
SN	Simple parabolic	Normal
DN	Double parabolic	Normal
SB	(Sapin) stepped	Bright anodised
DB	Double parabolic	Bright anodised
DM	Double parabolic	Matt anodised
PR	PRismatic	
OP	OPal	





St. Joseph Hospital



Astra Fluorescent Luminaire



St. Joseph Hospital

